

Alpha Elite Alphanumeric Pager

Communications on the move

Ultimate Flexibility

The Alpha Elite supports flex technology and exciting capabilities in messaging. The Elite represents the functionality required of a business pager. It promotes a 4-line display with a zoom facility to a 2-line. Its can receive messages of up to 240 characters in length. The Alpha Elite has Optimax EL Electra light display.

The Alpha Elite message pager is part of the TH Comms business product range.

Greater Versatility

For absolute discretion the Alpha Elite can be programmed to alert you silently to an incoming message or you can choose from a wide selection of audible alerts.

Faster Communication

The Alpha Elite pager can be connected to any network and is available in VHF. If you connect to the PageOne network, you can rely on your message coming through in seconds because PageOne uses advanced satellite technology to send the message to transmitter sites across the country and through to you.

Product Features

- 4-line LCD display or 2-line zoom feature with 20 characters per line
- Total 32KB characters message memory capacity
- Optimax EL Electra light display and EL turn on
- Clear time of day and date display
- Time stamped messages
- PPS optional 10 canned messages
- Built-in 12/24 hour clock and alarm, including message alarm function

- User selectable alerts; vibrate, standard & chirping alerts
- Reminder alert on unread messages
- Graphic battery gauge indicator
- Memory full indicator
- Duplicate message management
- Holds up to 2,025 characters for private messages & 5,025 characters for mail drop messages

Specification

- Frequency Range: VHF 143-174 MHz
- Baud Rate: 1600/3200/6400
- Code Format: FLEX
- Sensitivity: 1600: ≤ 8 , 3200: ≤ 11 , 6400: ≤ 13.5 uV/m
- Selectivity: ≥ 55 dB
- Dimensions: 8.1cm x 5.5cm x 1.85cm
- Frequency Stability: $\leq \pm 15$ ppm
- Channel Spacing: 25 kHz (narrow band available)
- Receiver Type: Synthesized
- Address Capacity: 16 addresses
- Frequency Deviation: ± 4.8 kHz
- Alert Tone SPL: ≥ 78 dB @ 12 in (2700 Hz standard alert)
- Colour: Black
- Operating temperature: 5° to 40° C
- Storage temperature: -40° to +85° C

Battery Specification

- Battery: 1.5 volt 'AA' size Alkaline
- Battery life: (based on auto baud detect collapse = 4 90 days
- Low Battery alert level: 1.24 volts



The Alpha Elite message pager combines a stylish compact design with extremely powerful message handling capacity, giving you the ability to communicate on your own terms at all times.