

NP-88 Numeric Pager

Communications on the move

Ultimate Flexibility

The NP-88 offers accessibility to stay on top of your busy lifestyle. The NP-88 provides a simple but reliable solution. Incorporating the key functions required of a numeric pager; clear digit display, enhanced backlight and simple button functions.

The NP-88 numeric pager is part of TH Comms business product range.

Faster Communication

The NP-88 numeric pager can be connected to any network pending frequency. If you connect to the PageOne network, you can rely on your message coming through in seconds because PageOne uses advanced satellite technology to send the message to transmitter sites across the country and through to you.

Easy To Use

To send a message, simply dial your pager number with the prefix 07623 and using your touchtone telephone type in your message or contact the 24-hour Paging Call Centre, quote your pager number and leave the message with the Call Centre operator.

Product Features

Display:

- New improved backlight:
In low light conditions the backlight makes the screen easy to read
- Standby screen:
The standby screen displays the time of day/date or no display
- Time/Date:
The time of day/date is displayed whether the pager is on or off

Indicator /Alert:

- Low battery indicator:
When battery is low all pager alerts change to 2 seconds in length

- Personal Alarm
- Reminder alert:
The pager will vibrate or chirp every 2 minutes until you read all unread messages
- Selectable alerts:
A selection of 5 audible alert tones or vibrate option

Messaging:

- Duplicate message indicator
- Message deletion
- Memory capacity:
Stores up to 16 20-character messages
- Message protect:

Specifications

- Frequency Range: VHF 137-174 MHz
- Baud Rate: 512/1200/2400
- Code Format: FLEX & POCSAG
- Sensitivity: 512 Baud: ≤ -5.7 , 1200 Baud: ≤ -8 , 2400 Baud: ≤ -10.3 u/Vm
- Selectivity: ≥ 40 dB
- Dimensions: 8.1cm x 5.5cm x 1.85cm
- Frequency Stability: $\leq \pm 3.5$ ppm
- Channel Spacing: 25 kHz
- Receiver Type: Synthesized
- Frequency Deviation: ± 4.8 kHz
- Alert Tone SPL: ≥ 78 dB @ 12 inches (2700 Hz standard alert)
- Colour: Black
- Operating temperature: 5° to 40° C

Battery Specification

- Battery: 1.5 volt 'AAA' size Alkaline
- Battery life: (based on 2 pager per day: 24 hours on, full capacity collapse = 4-5 months
- Weight: 50.4g with battery



With the LS350 pager in your pocket or bag you need never miss out on that important business opportunity again. This pager works as either tone or numeric and is available with FLEX technology. The LS350 offers many enhanced features, including 30 message slots; the ability to save messages when changing the battery; time and date standby; three musical alerts and message time stamping.