

RT760 Alphanumeric Pager

Communications on the move



Ultimate Flexibility

The RT760 provides flexibility, allowing the user to set the pager to read as a 2 or 4-line pager. With personal and mail drop message options, the RT760 allows you to quickly and easily read, delete or save messages.

The unread message reminder alert ensures you never miss a message.

You can store up to 32 personal messages and 48 in the mail-drop folders. The pager contains a message capacity of 25,000 English characters.

The RT760 is part of the TH Comms CPP product range.

Greater Versatility

For ultimate discretion the TH Comms RT760 can be programmed to alert you silently to an incoming message or you can choose from a range of audible alerts and melodies.

Faster Communication

The RT760 is connected to the PageOne network. You can rely on your message coming through in seconds because PageOne uses advanced satellite technology to send the message to transmitter sites across the country and through to you.

Easy To Use

To send a message, callers simply dial your pager number; they will automatically be connected to the PageOne Call Centre and asked to leave a message. The RT760 is part of TH Comms

To find out more contact TH Comms on:

Telephone: +44 (0) 20 8914 5339 or email enquiries@thcomms.co.uk

Product Features

- 2 or 4 line pager. Four lines with 72 characters per page or 2 lines larger text size with 28 characters per screen
- Custom selectable power-on LCD screen
- LCD display with backlight
- Memory back-up during battery replacement
- 25,000 character capacity, 32 personal set messages & 48 mail-drop set messages
- Adjustable LCD contrast for easy night reading
- Timed, numbered and dated messages
- Built-in 12/24 hour clock and alarm
- Auto on/off function
- Choice of silent, vibrate alert or 4 kinds of beeps or 10 melodies audible alerts.
- Easy to use symbols and prompts
- Battery voltage measuring function
- Unread message alert every 3-minutes
- Ability to lock and delete messages

Specifications

- Dimensions: 68 x 47 x 17mm
- Sensitivity: 512 bps:5uv/m, 1200 bps:7uv/m, 2400 bps:9uv/m
- Selectivity: More than 60db
- Deviations: -4.5 Khz / +4.5 Khz
- Min. Operation Voltage: 1.10 + - 0.05 Khz10
- Weight: 50g (with battery)
- Frequency Stability: under ppm (-10~ +50)
- Modulation: FSK – NRZ
- Channel Spacing: 25 Khz
- Battery: 1.5 volt 'AAA' size Alkaline
- Colour: Black
- Languages available: English, Chinese, Russian, Spanish & Portuguese